PJD6220

LIGHT, BRIGHT AND PORTABLE PROJECTOR

with BrilliantColor™

Digital clarity in a portable projector.

The PJD6220 is the lightweight DLP® powerhouse that delivers sharp and bright images for virtually any environment. BrilliantColor™ technology produces more vibrant colors, while the high brightness and contrast ratios make this projector shine in virtually any lighting situation. This projector is designed for table-top use or can be mounted on the ceiling for classrooms and meeting rooms. RJ-45 connectivity enables remote network control, while the extensive input options and integrated 2x5-watt stereo speakers deliver a truly dynamic multimedia experience. This projector even features closed captioning for the hearing impaired. The PJD6220 is ideal for use in classrooms and corporate settings.

VERSATILE PRESENTATIONS MADE EASY

> **Network control through RJ-45**
Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector and lamp status.

> **Bright in virtually any setting with 2,300 lumens**
Packs 2,300 lumens in just 6.5 lbs. It's the bright choice for mobile presenters.

> **BrilliantColor technology**
DLP® projectors with BrilliantColor™ feature multi-color processing to produce nearly 50% brighter colors for a vibrant image on the screen that won't fade over time.

> **Closed captioning**
Integrated closed captioning decoder for the hearing impaired.

> **Easy lamp replacement**
Convenient top loading allows for quick and easy lamp replacement.

> **Eco-mode extends lamp life**
Extend the life of your lamp up to 4,000 hours* and reduce noise output.

> **One of the best warranties in the business**
Covered by a three-year limited parts warranty, 1-year lamp warranty and first-year free Express Exchange® service.

PICTURE BY DLP TEXAS INSTRUMENTS

FEATURES BrilliantColor™ With Multi-Color Processing For Rich, Vibrant Colors! DLP

MORE THAN 2000 AWARDS

VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic® See the difference™

PJD6220

ViewSonic® See the difference™

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH BrilliantColor™

Optional Accessories

> Replacement lamp	RLC-034
> Universal ceiling mount kit	WMK-005
> Wireless G presentation gateway	WPG-150
> 2nd & 3rd year extended warranty	PRJ-EE-03-03

Projection Distance 4:3 Screen		Screen Size 4:3 Screen	
m	feet	m	Inch
1.2	3.94	1.0-0.8	27.3-30.1
2	6..65	1.2-1.3	45.6-50.0
3	9.84	1.7-1.9	68.4-74.9
5	16.4	2.9-3.2	113.9-124.9
10	32.81	5.8-6.4	227.8-249.8

RoHS COMPLIANT™

ISO 9001:2000 FM 40187 — ISO 14001:1996 FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DISPLAY	Type	0.55" Digital Micromirror Device (DLP®)
	Resolution	XGA 1024x768 (native) / SXGA 1280x1024 (compressed)
	Lens	1.1× Manual Optical Zoom / Manual focus
	Keystone	Vertical Digital keystone correction: +/- 40 degrees
	Size	30"-300" (Diagonal) / 0.8m-7.6m
	Throw Distance	1.2m-10m (47"-393")
	Throw Ratio	1.97:1~2.16:1
	Lamp	180 watt
	Lamp Life (Normal / Eco Mode)	3500 / 4000* (hours)
	Brightness	2,300 Lumens
	Contrast Ratio	2000:1 (typ)
	Aspect Ratio	4:3 (native) / 16:9
	Color Gamut	85% NTSC (CIE 1931)
AUDIO	Speakers	2 × 5w
INPUT SIGNAL	Computer and Video	RGB analog, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N, 60), SECAM, SDTV / EDTV (480i/p, 576i/p), HDTV (720p, 1080i/p)
	Frequency	Fh: 15-100 KHz, Fv: 43-85 Hz
COMPATIBILITY	PC	Analog /: VGA up to SXGA (scaled)
	Mac	Analog /: up to XGA (scaled)
CONNECTOR	RGB Input / Output	2 × in / 1× out (15-pin D-sub)
	Composite Input	1× RCA jack
	S-Video Input	1× 4-pin mini-DIN
	Audio Input / Output	in ×1 / out ×1 (3.5mm Mini Jack)
	USB	1× USB type B (firmware upgrade only)
	Control	1× RS232 (6 pin D-Sub)
	Network	1×RJ-45
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	265W (typ.) / 9W (Stand-by mode)
CONTROLS	Basic	Standby / On, input, menu
	OSD	**Picture:** brightness, contrast, color setting, keystone, aspect ratio,image, white intensity, gamma **Computer image:** frequency, tracking, H position, V position **Video image:** saturation, sharpness, tint **Sound:** volume, mute **Setting:** menu position, projection, signal type, lamp hour, lamp hour reset, power saving, auto source, ECO mode, high altitude, OSD timeout **Option:** blank screen, start-up screen, screen capture, password, DCR, closed caption, network control, BrilliantColor™ **Network config:** DHCP, IP address, subnet mask, gateway **Factory default**
OPERATING CONDITION	Temperature	32°F-104°F (0°C-40°C)
	Humidity	10% - 80% (non-condensing)
	Altitude	0 to +10,000 ft (3,048 m)
NOISE LEVEL		36 (Normal) / 34 (Eco-mode)
DIMENSIONS	W x H x D	8.93" x 4.3" x 8.77" (271mm× 110mm × 223mm)
WEIGHT	Net	6.5 lbs (2.9 kg)
	Gross	11.1 lbs (5.0 kg)
REGULATIONS		CB, UL/cUL, FCC-B, ICES-003, IRAM, NOM, CE, GS, GOST- R, Hygienic, SASO, UKrSEPRO, CCC, C-tick, EK, RoHS
PACKAGE CONTENTS		Projector, Power cable, VGA cable, Remote control with batteries, Composite cable, S-video cable, Soft carrying case, Lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide), VGA-component adapter
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running eco-mode exclusively can extend lamp life. DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14307-00B-02/09] PJD6220-1